

NYLON RECOVERY STROPS

High Strength, Heavy Duty

DESCRIPTION

The Black Snake Nylon Recovery Strop is a heavy-duty, industrial-strength alternative to traditional webbing straps and nylon ropes. It features nylon strands in a parallel lay construction, embedded in galvanised thimbles, and covered with vulcanised rubber for durability and protection. This design shields the load-bearing fibres from abrasion, dirt, and mud, making it virtually maintenance-free. With a high-strength Nylon 6.6 core, it's lightweight, flexible, and easy to install, offering up to 20% stretch for snatch recoveries. It also includes a serial number and RFID for traceability, making it ideal for harsh environments with superior durability, low shock load, and high break strength.

Break Strength	Part Number & Weight in KG				
	3 Mtr	6 Mtr	10 Mtr	15 Mtr	20 Mtr
8 Tonne	12BS0803N 3Kg	12BS0806N 4Kg	12BS0810N 6Kg	12BS0815N 8Kg	12BS0820N 11Kg
12 Tonne	12BS1203N 4Kg	12BS1206N 6Kg	12BS1210N 8Kg	12BS1215N 11Kg	12BS1220N 14Kg
20 Tonne	12BS2003N	12BS2006N 8Kg	12BS2010N 12Kg	12BS2015N 16Kg	12BS2020N 21Kg
30 Tonne	12BS3003N	12BS3006N 12Kg	12BS3010N 18Kg	12BS3015N 25Kg	12BS3020N 30Kg
50 Tonne	12BS5003N	12BS5006N 20Kg	12BS5010N 32Kg	12BS5015N 42Kg	12BS5020N 56Kg
70 Tonne	12BS7003N	12BS7006N 25Kg	12BS7010N 40Kg	12BS7015N 58Kg	12BS7020N 77Kg
100 Tonne	12BS1003N	12BS10006N 40Kg	12BS10010N 65Kg	12BS10015N 85Kg	12BS10020N 109Kg



NYLON RECOVERY STROPS

High Strength, Heavy Duty

FEATURES

- **Heavy-duty nylon strands with galvanised thimbles:** Durable and protected from cutting and fraying.
- **Abrasion-resistant rubber casing:** Shields inner fibres from dirt, oil, water, and mud, making it low-maintenance.
- **High-strength Nylon 6.6 core:** Lightweight, with superior strength and durability compared to fabric straps.
- **Up to 20% stretch for snatch recoveries:** Reduces shock loads and enhances energy dampening.
- **Serial numbers and RFID:** Ensures easy traceability and accurate record-keeping.

Break Strength	Maximum GVW ² Severely bogged vehicle ³	Thimble size	Recommended Gr-S Shackle	Recommended Coupling Link
8 Tonne	5 Tonne	16mm	3.25 - 6.5 Tonne	13mm
12 Tonne	8 Tonne	22mm	6.5 - 8.5 Tonne	13-16mm
20 Tonne	13 Tonne	24mm	6.5 - 12 Tonne	16mm
30 Tonne	20 Tonne	28mm	8.5 - 17 Tonne	18/20mm
50 Tonne	33 Tonne	36mm	12 - 35 Tonne	26mm
70 Tonne	46 Tonne	44mm	25 - 35 Tonne	32mm
100 Tonne	67 Tonne	52mm	25 - 55 tonne	32mm

