

GRADE 80 SINGLE LEG CHAIN SLING WITH SAFETY LATCH HOOK

Our pre-assembled Grade 80 Single Leg Chain Slings with Safety Latch Hook are made with grade 80 chain and are supplied with either clevis self-locking hooks or clevis safety latch hooks as terminal fittings. They are available in different lengths, and are adjustable via grab hooks. These slings are perfect for use in the construction, infrastructure, and mining sectors, and are very useful in a broad range of industrial lifting applications.

Features

- Adjustable with grab shortener hooks at top
- Safety latch/sling hook on bottom of chains
- Supplied assembled, tested and certified
- Comes with test certificate
- Meets Australian Standard AS 3775
- Other sizes, configurations and capacities available upon request



PRODUCT SPECIFICATIONS

All Lifting Grade 80 (T) Chain Slings to AS3775.2-2014

Chain Dia. mm	Single Leg Slings			Slings of 2, 3 or 4 legs				
	Straight Sling	Adjustable & Reeved Sling	Basket Sling Max 60°	Straight Sling			Reeved Sling Max 60°	Basket Sling Max 60°
				60°	90°	120°		
6.0	1.1	0.8	1.5	1.9	1.6	1.1	1.5	2.5
7.0	1.5	1.1	2.0	2.6	2.1	1.5	2.0	3.4
8.0	2.0	1.5	2.6	3.5	2.8	2.0	2.6	4.5
10.0	3.2	2.4	4.1	5.5	4.5	3.2	4.1	7.2
13.0	5.3	4.0	6.9	9.2	7.5	5.3	6.9	11.9
16.0	8.0	6.0	10.4	13.8	11.3	8.0	10.4	18.0
20.0	12.5	9.4	16.3	21.6	17.6	12.5	16.3	28.1
22.0	15.0	11.3	19.5	26.0	21.2	15.0	19.5	33.8
26.0	21.2	15.9	27.6	36.7	29.9	21.2	27.6	47.7
32.0	31.5	23.6	41.0	54.5	44.4	31.5	41.0	70.9

Working load limit in tonnes under general conditions of use.
Safety Factor 4:1