

# TRANSPORT ROLLER SKATES

## Description

Shifting skate can be used wherever heavy objects have to be moved. The load can be lifted using either the roller crowbar or a jack, allowing the skates to be easily positioned. The large diameter sealed nylon roller ensure ease of movement and spread the load, protecting high quality floors from damage caused by high point loads and oil/grease contamination. The skates are maintenance free and are fitted with handles for ease of carrying and positioning.

Turnable with bearings; Friction Coefficient: 0.15 to 0.25

### Model: RSA



Product code	Capacity (Ton)	Wheel NO.	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)
10LS060	6	4	300	225	110	13.15
10LS080	8	6	400	225	110	15.80
10LS0120	12	8	500	225	110	25.91
10LS0180	18	12	500	313	110	40.93

Minimum turning circle is 3 meters

### Model: RSO



Fixed skate type; Friction Coefficient: 0.15 to 0.25

Product code	Capacity (Ton)	Wheel NO.	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)
10LS06	6	4	300	225	100	11.89
10LS08	8	6	400	225	100	14.55
10LS12	12	8	500	225	100	24.65
10LS18	18	12	500	313	100	39.67

Minimum turning circle is 3 meters